



ENJOY YOUR DAY  
with EDGE

79 Saneopro 156-gil, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea  
marketing.robotics@doosan.com | +82-31-8014-5500

7950 Legacy Drive, Ste. 550, Plano, TX 75024  
americas.robotics@doosan.com | +1 469885 5722

[in](#) [v](#) [f](#) [Q](#) Doosan Robotics

[@doosan\\_robotics](#) [doosanrobotics](#)

Lineup for the Food & Beverage Industry **E0509**

# Enjoy your day with EDGE!

The E-SERIES stands out as the ultimate collaborative robot (cobot) for the food and beverage industry. With its exceptional features, including unmatched adaptability NSE certification, and IP66 rating, this cobot is specifically designed to enhance productivity in any environment.



**5 kg** Payload  
**0.05 mm** Repeatability  
**IP66** Protection Rating

- The world's first collaborative robot dedicated to the food and beverage industry
- Hygienic design for sanitary food handling, prep, and cooking
- Industry-leading safety features

## Features



### NSF-Certified\*

The E-SERIES is NSF-certified to meet compliance and health codes in any food or beverage prep space



### Environmental Adaptation

With IP66 accreditation, the E-SERIES easily operates in temperatures up to 113°F or 45°C



### Easy Installation

The E-SERIES features an all-in-one package design that is 62% smaller than previous models, making it incredibly compact and convenient for transport and installation



### Affordable

The E-SERIES is a cost-effective automation solution, ensuring rapid ROI in as few as 14 months



### Safe

With its industry-leading safety certifications\*\*, the E-SERIES effectively minimizes risks and injuries in busy workspaces



### Hygienic

The E-SERIES incorporates a gap-less design and a high-gloss, food-safe finish, enabling effortless cleaning and ensuring sanitary operation

## Specifications

### E0509 ARM

Payload	5 kg
Reach	900 mm
Tool Speed	1 m/s Over
Joint - Range (°)	±[360 360 155 360 155 360]
Joint - Speed (°/sec.)	[120 120 150 225 225 225]
Repeatability	± 0.05 mm
Weight	22.5 kg
Protection Rating	IP66
Temperature	0~45°C
Noise Level	< 60 dB(A)
Cable	6 m
Cable Holder	Yes (Option)
NSF	Food zone (Indirect)

### Controller

Weight	9 kg
Dimension(mm)	440 x 400 x 91.2
Teaching Method	DART-Platform (PC/Surface;sold separately)
Option	DC Controller, Smart Pendant



DC Controller



Smart Pendant

### Safety

Safety Rating	STO, SBC, EMG: PL e Cat. 4, SIL 3 Other features: PL d Cat. 3, SIL 2
---------------	---

\*National Sanitation Foundation  
 \*\*PL e · Cat. 4